

S Flex Series

17.3%

Module efficiency

3year

Quality/Performance Warranty

100-105W Mono PERC Flexible Module



- ★ ISO 9001: 2015 Quality Management System
- ★ ISO 45001: 2018 Occupation Health Safety Management System
- ★ ISO 14001: 2015 Environment Management System

Features



Light, Thin design

1.7kg weight, match various requirements for low-load projects



Full Black

All black design for more elegant applications



Ultra Flexible

Ultra-thin silicon wafers with advanced organic polymer encapsulation materials, minimum bending radius reach 0.30m, fit all kinds of curved surface perfectly



High Efficiency And Reliability

Busbar-free design increases cell conversion efficiency, more power output can be achieved at low irradiance conditions



Convenient Installation

Easy installation and convenient transportation with lower cost



Lead-free

Eco-friendly PV design achieves lead-free MWT module without soldering materials

Electrical Characteristics at Standard Test Conditions(STC)


Spec/Model	Unit	100W	105W
Max-Power(Pm)	W	100	105
Power Tolerance	W	0~+5	
Max-Power Voltage(Vm)	V	20.4	20.6
Max-Power Current(Im)	A	4.91	5.11
Open-Circuit Voltage(Voc)	V	24.6	24.8
Short-Circuit Current(Isc)	A	5.22	5.42
Effective Module Efficiency(nm)	%	16.5	17.3
STC: AM=1.5, Irradiation 1000W/m ² , Module Temperature 25°C			

Electrical Characteristics at Nominal Module Operating Temperature (NMOT)


Spec/Model	Unit	100W	105W
Max-Power(Pm)	W	72	76
Max-Power Voltage(Vm)	V	18.5	18.7
Max-Power Current(Im)	A	3.89	4.06
Open-Circuit Voltage(Voc)	V	22.5	22.7
Short-Circuit Current(Isc)	A	4.21	4.38
NMOT: Irradiation 800W/m ² , Ambient temperature 20°C, Wind Speed 1m/s			

I-V Curve

I-V Curves of 100W at different irradiance



I-V Curves of 100W at different cell temperature



Temperature Coefficient

Nominal Module Operating Temperature	43±2°C
Temperature coefficient of Pmax	-0.36%/°C
Temperature coefficient of Voc	-0.28%/°C
Temperature coefficient of Isc	0.06%/°C

Mechanical Characteristics

Installation Module Dimension (L×W×H)	1075mm×565mm×2.3mm
Weight	1.7 kg
Back material	Back Sheet(black)
Cell (quantity / material / type / dimensions)	36(6x6)/Mono /166*83mm /φ223mm
Frame	
Junction box(protection degree)	IP68
Cable (length/cross-section area)	Customizable/ 4mm ²
Connector	MC4 Compatible

Module Size

